


**VOLTAGE RANGE: 50 - 1000V**

**CURRENT: 5.0 A**




### Features

- Glass Passivated Die Construction
- Ideally Suited for Automatic Assembly
- Low Forward Voltage Drop, High Efficiency
- Low Power Loss
- Ultra-Fast Recovery Time
- Plastic Case Material has UL Flammability Classification Rating 94V-O

### Mechanical Data

- Case: SMC/DO-214AB, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.21 grams (approx.)



SMC/DO-214AB		
Dim	Min	Max
A	5.59	6.22
B	6.60	7.11
C	2.75	3.18
D	0.15	0.31
E	7.75	8.13
G	0.10	0.20
H	0.76	1.52
J	2.00	2.62
All Dimensions in mm		

### Maximum Ratings and Electrical Characteristics T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	UF5A	UF5B	UF5D	UF5G	UF5J	UF5K	UF5M	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V
Maximum average forward rectified current 0.375" (9.5mm) lead length at T <sub>A</sub> =55°C	I <sub>(AV)</sub>	5.0							A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	150.0							A
Maximum instantaneous forward voltage at 5.0A	V <sub>F</sub>	1.0		1.40		1.70		V	
Maximum DC reverse current at rated DC blocking voltage	I <sub>R</sub>	10.0		300.0				μA	
Maximum reverse recovery time (NOTE 1)	t <sub>rr</sub>	50				75		ns	
Typical junction capacitance (NOTE 2)	C <sub>J</sub>	15				12		pF	
Typical thermal resistance (NOTE 3)	R <sub>θJL</sub>	15.0							°C/W
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-65 to +150							°C


- Note:**
1. Reverse recovery condition I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>rr</sub>=0.25A
  2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
  3. Thermal resistance from junction to lead and from junction to ambient with P.C.B mounted  
0.03" x 0.3" (8.0 x 8.0 mm) Copper pad area



**RATINGS AND CHARACTERISTIC CURVES UF5A THRU UF5M**


AVERAGE FORWARD RECTIFIED CURRENT, AMPERES

**FIG. 1- FORWARD CURRENT DERATING CURVE**




PEAK FORWARD SURGE CURRENT, AMPERES

**FIG. 2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**




**FIG. 3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**




INSTANTANEOUS REVERSE CURRENT, MICROAMPERES

**FIG. 4- TYPICAL REVERSE CHARACTERISTICS**



**FIG. 5- TYPICAL JUNCTION CAPACITANCE**



TRANSIENT THERMAL IMPEDANCE, °C/W

**FIG. 6- TYPICAL TRANSIENT THERMAL IMPEDANCE**

