




## Technical Data Sheet

### Opto Interrupter

ITR8307/S17/TR8

#### Features

- Fast response time
- High sensitivity
- Cut-Off visible wavelength
- Thin
- Compact
- Pb free
- This product itself will remain within RoHS compliant version.



#### Descriptions

**ITR8307/S17/TR8** is a light reflection switch which includes a GaAs IR-LED transmitter and a NPN photo-transistor with a high photosensitive receiver for short distance, operating in the infrared range. Both components are mounted side- by- side in a plastic package.

#### Applications

- Camera
- VCR
- Floppy disk driver
- Cassette type recorder
- Various microcomputer control equipment

#### Device Selection Guide


| Device No. | Chip Material |
|------------|---------------|
| IR         | GaAs          |
| PT         | Silicon       |

# Technical Data Sheet

## Opto Interrupter

**ITR8307/S17/TR8**

### Package Dimensions



①: CATHODE      ③: COLLECTOR  
②: ANODE      ④: EMITTER

**Notes:** 1. All dimensions are in millimeters  
2. Tolerances unless dimensions  $\pm 0.15\text{mm}$

### Absolute Maximum Ratings ( $T_a=25^\circ\text{C}$ )

| Parameter                       |   | Symbol      | Ratings        | Unit             |
|---------------------------------|---|-------------|----------------|------------------|
| Input                           | Power Dissipation at (or below) $25^\circ\text{C}$ Free Air Temperature         | $P_d$       | 75             | mW               |
|                                 | Reverse Voltage   | $V_R$       | 5              | V                |
|                                 | Forward Current   | $I_F$       | 50             | mA               |
|                                 | Peak Forward Current (*1)<br>Pulse width $\leq 100 \mu\text{s}$ , Duty cycle=1% | $I_{FP}$    | 1              | A                |
| Output                          | Collector Power Dissipation   | $P_C$       | 75             | mW               |
|                                 | Collector Current   | $I_C$       | 50             | mA               |
|                                 | Collector-Emitter Voltage   | $B V_{CEO}$ | 30             | V                |
|                                 | Emitter-Collector Voltage   | $B V_{ECO}$ | 5              | V                |
| Operating Temperature           |   | $T_{opr}$   | $-25 \sim +85$ | $^\circ\text{C}$ |
| Storage Temperature             |   | $T_{stg}$   | $-30 \sim +90$ | $^\circ\text{C}$ |
| Lead Soldering Temperature (*2) |   | $T_{sol}$   | 260            | $^\circ\text{C}$ |

(\*1)  $t_w=100 \mu\text{sec.}$ ,  $T=10 \text{ msec.}$       (\*2)  $t=5 \text{ Sec}$



# Technical Data Sheet

## Opto Interrupter

ITR8307/S17/TR8

### Electro-Optical Characteristics (Ta=25°C)

| Parameter                |                        | Symbol        | Min. | Typ. | Max. | Unit            | Conditions                                    |
|--------------------------|------------------------|---------------|------|------|------|-----------------|---|
| Input                    | Forward Voltage        | $V_F$         | ---  | 1.2  | 1.6  | V               | $I_F=20\text{mA}$                             |
|                          | Reverse Current        | $I_R$         | ---  | ---  | 10   | $\mu\text{A}$   | $V_R=5\text{V}$                               |
|                          | Peak Wavelength        | $\lambda_p$   | ---  | 940  | ---  | nm              | ---   |
| Output                   | Dark Current           | $I_{CEO}$     | ---  | ---  | 100  | nA              | $V_{CE}=10\text{V}$                           |
|                          | C-E Saturation Voltage | $V_{CE(sat)}$ | ---  | ---  | 0.4  | V               | $I_C=2\text{mA}$<br>$E_e=1\text{mW/cm}^2$     |
| Transfer Characteristics | Light Current          | $I_C(ON)$     | 0.18 | ---  | 0.44 | mA              | $V_{CE}=5\text{V}$                            |
|                          | Leakage Current        | $I_{CEO}$     | ---  | ---  | 1    | $\mu\text{A}$   | $I_F=10\text{mA}$                             |
|                          | Rise time              | $t_r$         | ---  | 20   | ---  | $\mu\text{sec}$ | $V_{CE}=2\text{V}$                            |
|                          | Fall time              | $t_f$         | ---  | 20   | ---  | $\mu\text{sec}$ | $I_C=100\mu\text{A}$<br>$R_L=1\text{K}\Omega$ |

### Rank

Conditions :  $I_F=10\text{mA}$   $V_{CE}=5\text{V}$ Unit:  $\mu\text{A}$ 

| Bin number | Min | Max |
|------------|-----|-----|
| B          | 180 | 300 |
| C          | 250 | 440 |

# Technical Data Sheet

## Opto Interrupter

**ITR8307/S17/TR8**

### Typical Electrical/Optical/Characteristics Curves for IR

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Spectral Distribution




Fig. 3 Peak Emission Wavelength vs. Ambient Temperature




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Forward Voltage vs. Ambient Temperature





Fig. 6 Relative Radiant Intensity vs. Angular Displacement



### Typical Electro/Optical/Characteristics Curves for PT

# Technical Data Sheet

## Opto Interrupter

**ITR8307/S17/TR8**

Fig.1 Collector Power Dissipation vs. Ambient Temperature




Fig.2 Collector Dark Current vs. Ambient Temperature




Fig. 3 Relative Collector Current vs. Ambient Temperature




Fig.4 Collector Current vs. Irradiance




Fig.5 Spectral Sensitivity





Fig.6 Collector Current vs. Collector-emitter Voltage



### Typical Electrical/Optical/Characteristics Curves For ITR

# Technical Data Sheet

## Opto Interrupter

**ITR8307/S17/TR8**

Fig.1 Relative Collector Current vs. Distance between Sensor and Al Evaporation Galss





Fig.2 Relative Collector Current vs. Card Moving Distance (l)







Fig.3 Response Time vs. Load Resistance



### Reliability Test Item And Condition

The reliability of products shall be satisfied with items listed below.



# Technical Data Sheet

## Opto Interrupter

ITR8307/S17/TR8

Confidence level : 90%

LTPD : 10%

| NO. | Item                               | Test Conditions  | Test Hours/<br>Cycles | Sample<br>Sizes | Failure<br>Judgement<br>Criteria  | Ac/Re |
|-----|------------------------------------|--|-----------------------|-----------------|---|-------|
| 1   | Solder Heat                        | TEMP. : $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$  | 10secs                | 22pcs           | $I_R \geq U \times 2$<br>$E_e \leq L \times 0.8$<br>$V_F \geq U \times 1.2$<br><br>U : Upper<br>Specification<br><br>Limit<br>L : Lower<br>Specification<br>Limit | 0/1   |
| 2   | Temperature Cycle                  | H : $+85^{\circ}\text{C}$ 30mins<br>$\updownarrow$ 5mins<br>L : $-55^{\circ}\text{C}$ 30mins | 50Cycles              | 22pcs           |   | 0/1   |
| 3   | Thermal Shock                      | H : $+100^{\circ}\text{C}$ 5mins<br>$\updownarrow$ 10secs<br>L : $-10^{\circ}\text{C}$ 5mins | 50Cycles              | 22pcs           |   | 0/1   |
| 4   | High Temperature Storage           | TEMP. : $+100^{\circ}\text{C}$   | 1000hrs               | 22pcs           |   | 0/1   |
| 5   | Low Temperature Storage            | TEMP. : $-55^{\circ}\text{C}$  | 1000hrs               | 22pcs           |   | 0/1   |
| 6   | DC Operating Life                  | $I_F = 20\text{mA}$  | 1000hrs               | 22pcs           |   | 0/1   |
| 7   | High Temperature/<br>High Humidity | $85^{\circ}\text{C}$ / 85% R.H   | 1000hrs               | 22pcs           |   | 0/1   |

### Recommended Method of Storage

The following are general recommendations for moisture sensitive level (MSL) 4 storage and use:


- Shelf life in sealed bag: 12 months at  $< 40^{\circ}\text{C}$  and  $< 90\%$  relative humidity (RH)

# Technical Data Sheet

## Opto Interrupter


**ITR8307/S17/TR8**

- After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
  - a) Mounted within 72 hours of factory conditions  $< 30^{\circ}\text{C}/60\%\text{RH}$ , or
  - b) Stored at  $<20\%\text{RH}$
- Devices require bake, before mounting, if:
  - Humidity Indicator Card is  $> 20\%$  when read at  $23 \pm 5^{\circ}\text{C}$
- If baking is required, devices may be baked:
  - a) 192 hours at  $40^{\circ}\text{C}$ , and  $<5\%\text{RH}$ (dry air/nitrogen) or
  - b) 96 hours at  $60^{\circ}\text{C}$ , and  $<5\%\text{RH}$  for all device containers
  - c) 24 hours at  $125^{\circ}\text{C}$
- Soldering Condition
  - a) Pb-free solder temperature profile



- b) Reflow soldering should not be done more than two times.
- c) When soldering, do not put stress on the LEDs during heating.
- d) After soldering, do not warp the circuit board.
- Repairing


Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



## Taping Dimension


Progressive direction →

Everlight Electronics C  
Device No : DRX-083




Page: 8 of 10  
Ming-jing Lee



**Technical Data Sheet**  
**Opto Interrupter****ITR8307/S17/TR8****Reel Dimensions**

**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

**Moisture Resistant Packaging****Packing Quantity Specification**

1. 1000 Pcs/ 1Reel
2. 15 Reel /1 Box



## Technical Data Sheet Opto Interrupter

ITR8307/S17/TR8

3. 2 Box/ 1 Carton

### Label Form Specification

The diagram shows a rectangular label with the following layout:

- Top center: **EVERLIGHT** logo in a box.
- Top right: A small circle.
- Left side, top: CPN: P/N:
- Left side, middle: A large barcode.
- Left side, bottom: ITR8307/S18/TR8
- Right side, middle: **RoHS** in a box.
- Left side, bottom: QTY: LOT NO:
- Right side, bottom: CAT: HUE: REF:
- Bottom center: A large barcode.
- Bottom center: MADE IN TAIWAN

CPN: Customer's Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: None

HUE: None

REF: Reference

LOT No: Lot Number

MADE IN TAIWAN: Production Place

### Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.