



授权光宝代理



联系：企业QQ2881817135

电话：0755-82550289



# Photocoupler Product Data Sheet LTV-354T

Spec No. :DS70-2001-004  
Effective Date: 09/12/2018  
Revision: N

**LITE-ON DCC**

**RELEASE**

BNS-OD-FC001/A4

## Photocoupler LTV-354T series

### 1. DESCRIPTION

#### 1.1 Features

- AC input response
- Current transfer ratio ( CTR : MIN. 20% at  $I_F = \pm 1\text{mA}$ ,  $V_{CE} = 5\text{V}$  )
- High input-output isolation voltage (  $V_{ISO} = 3,750\text{Vrms}$  )
- Mini-flat package : LTV-354T series
- Safety approval
  - UL 1577 & cUL
  - VDE DIN EN60747-5-5 (VDE 0884-5) ,
  - CSA CA5A
  - CQC GB4943.1-2011/ GB8898-2011
  - FIMKO/DEMKO/SEMKO/NEMKO
- RoHS Compliance
  - All materials be used in device are followed EU RoHS directive (No.2002/95/EC, 2011/65/EU, and 2015/863).
- ESD pass HBM 8000V/ MM2000V /CDM2000V
- MSL class1
- Halogen Free option


#### 1.2 Applications

- Hybrid substrates that require high density mounting.
- Programmable controllers
- System appliance, measuring instruments

## Photocoupler LTV-354T series

### 2. PACKAGE DIMENSIONS

#### 2.1 LTV-354T series



#### Notes :


- 1-digit year code, Example : 2010 = A  
2-digit work week ranging from '01' to '53'
- Factory identification mark shall be marked (W: China -CZ, X: China -TJ)
- Rank shall be or shall not be marked.
- "●" indicates halogen free option.
- "V" for VDE option.

\*All dimensions in millimeters.


## Photocoupler LTV-354T series

### 3. TAPING DIMENSIONS

#### 3.1 LTV-354T-TP



#### 3.2 LTV-354T



| Description                            | Symbol         | Dimension in mm (inch) |
|----------------------------------------|----------------|------------------------|
| Tape wide                              | W              | 12 $\pm$ 0.3 (0.472)   |
| Pitch of sprocket holes                | P <sub>0</sub> | 4 $\pm$ 0.1 (0.157)    |
| Distance of compartment                | F              | 5.5 $\pm$ 0.1 (0.217)  |
|                                        | P <sub>2</sub> | 2 $\pm$ 0.1 (0.079)    |
| Distance of compartment to compartment | P <sub>1</sub> | 8 $\pm$ 0.1 (0.315)    |

#### 3.3 Quantities Per Reel

| Package Type     | LTV-354T series |
|------------------|-----------------|
| Quantities (pcs) | 3000            |

## Photocoupler LTV-354T series

### 4. RATING AND CHARACTERISTICS

#### 4.1 Absolute Maximum Ratings at Ta=25°C

|        | Parameter                   | Symbol    | Rating     | Unit      |
|--------|-----------------------------|-----------|------------|-----------|
| Input  | Forward Current             | $I_F$     | ±50        | mA        |
|        | Power Dissipation           | P         | 70         | mW        |
|        | Junction Temperature        | $T_J$     | 125        | °C        |
| Output | Collector - Emitter Voltage | $V_{CEO}$ | 35         | V         |
|        | Emitter - Collector Voltage | $V_{ECO}$ | 6          | V         |
|        | Collector Current           | $I_C$     | 50         | mA        |
|        | Collector Power Dissipation | $P_C$     | 150        | mW        |
|        | Junction Temperature        | $T_J$     | 125        | °C        |
|        | Total Power Dissipation     | $P_{tot}$ | 170        | mW        |
| 1.     | Isolation Voltage           | $V_{iso}$ | 3750       | $V_{rms}$ |
|        | Operating Temperature       | $T_{opr}$ | -55 ~ +110 | °C        |
|        | Storage Temperature         | $T_{stg}$ | -55 ~ +150 | °C        |
| 2.     | Soldering Temperature       | $T_{sol}$ | 260        | °C        |

1. AC For 1 Minute, R.H. = 40 ~ 60%

Isolation voltage shall be measured using the following method.

- (1) Short between anode and cathode on the primary side and between collector and emitter on the secondary side.
- (2) The isolation voltage tester with zero-cross circuit shall be used.
- (3) The waveform of applied voltage shall be a sine wave.

2. For 10 Seconds

## Photocoupler LTV-354T series

### 4.2 ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C

|        | Parameter                            | Symbol        | Min.              | Typ.              | Max. | Unit          | Test Condition                                         |
|--------|--------------------------------------|---------------|-------------------|-------------------|------|---------------|--------------------------------------------------------|
| Input  | Forward Voltage                      | $V_F$         | —                 | 1.2               | 1.4  | V             | $I_F=\pm 20\text{mA}$                                  |
|        | Terminal Capacitance                 | $C_t$         | —                 | 30                | 250  | pF            | $V=0, f=1\text{KHz}$                                   |
| Output | Collector Dark Current               | $I_{CEO}$     | —                 | —                 | 100  | nA            | $V_{CE}=20\text{V}, I_F=0$                             |
|        | Collector-Emitter Breakdown Voltage  | $BV_{CEO}$    | 35                | —                 | —    | V             | $I_C=0.1\text{mA}, I_F=0$                              |
|        | Emitter-Collector Breakdown Voltage  | $BV_{ECO}$    | 6                 | —                 | —    | V             | $I_E=10\mu\text{A}, I_F=0$                             |
|        | Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | —                 | 0.1               | 0.2  | V             | $I_F=\pm 20\text{mA}$<br>$I_C=1\text{mA}$              |
|        | Isolation Resistance                 | $R_{iso}$     | $5\times 10^{10}$ | $1\times 10^{11}$ | —    | $\Omega$      | DC500V,<br>40 ~ 60% R.H.                               |
|        | Floating Capacitance                 | $C_f$         | —                 | 0.6               | 1    | pF            | $V=0, f=1\text{MHz}$                                   |
|        | Response Time (Rise)                 | $t_r$         | —                 | 4                 | 18   | $\mu\text{s}$ | $V_{CE}=2\text{V}, I_C=2\text{mA}$<br>$R_L=100\Omega,$ |
|        | Response Time (Fall)                 | $t_f$         | —                 | 3                 | 18   | $\mu\text{s}$ |                                                        |

授权光宝代理



联系：企业QQ2881817135

电话：0755-82550289

## Photocoupler LTV-354T series

### 5. RANK TABLE OF CURRENT TRANSFER RATIO (CTR)

| CTR Rank | Min | Max | Condition                                                                |
|----------|-----|-----|--------------------------------------------------------------------------|
| GR       | 100 | 300 | $I_F = \pm 5\text{mA}$ , $V_{CE} = 5\text{V}$ , $T_a = 25^\circ\text{C}$ |
| A        | 50  | 150 | $I_F = \pm 1\text{mA}$ , $V_{CE} = 5\text{V}$ , $T_a = 25^\circ\text{C}$ |
| B        | 80  | 400 |                                                                          |
| B2       | 100 | 400 |                                                                          |
| No mark  | 20  | 400 |                                                                          |

$$\text{CTR} = \frac{I_C}{I_F} \times 100\%$$

## Photocoupler LTV-354T series

### 6. CHARACTERISTICS CURVES (TYPICAL PERFORMANCE)

Fig.1 Forward Current vs.  
Ambient Temperature




Fig.2 Collector Power Dissipation vs.  
Ambient Temperature




Fig.3 Collector-emitter Saturation  
Voltage vs. Forward Current




Fig.4 Forward Current vs. Forward  
Voltage




Fig.5 Current Transfer Ratio vs.  
Forward Current





Fig.6 Collector Current vs.  
Collector-emitter Voltage



# Photocoupler LTV-354T series

Fig.7 Relative Current Transfer Ratio  
vs. Ambient Temperature




Fig.8 Collector-emitter Saturation Voltage  
vs. Ambient Temperature




Fig.9 Collector Dark Current vs.  
Ambient Temperature




Fig.10 Response Time vs. Load  
Resistance







Fig.11 Frequency Response



Test Circuit for Response Time



Test Circuit for Frequency Response




## Photocoupler LTV-354T series

### 7. TEMPERATURE PROFILE OF SOLDERING

#### 7.1 IR Reflow soldering (JEDEC-STD-020C compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

| Profile item                     | Conditions     |
|----------------------------------|----------------|
| Preheat                          |                |
| - Temperature Min ( $T_{Smin}$ ) | 150°C          |
| - Temperature Max ( $T_{Smax}$ ) | 200°C          |
| - Time (min to max) ( $t_s$ )    | 90±30 sec      |
| Soldering zone                   |                |
| - Temperature ( $T_L$ )          | 217°C          |
| - Time ( $t_L$ )                 | 60 ~ 100 sec   |
| Peak Temperature ( $T_P$ )       | 260°C          |
| Ramp-up rate                     | 3°C / sec max. |
| Ramp-down rate                   | 3~6°C / sec    |



## Photocoupler LTV-354T series

### 7.2 Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature:  $260 \pm 0/-5^{\circ}\text{C}$

Time: 10 sec.

Preheat temperature: 25 to  $140^{\circ}\text{C}$

Preheat time: 30 to 80 sec.



### 7.3 Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.


Temperature:  $380 \pm 0/-5^{\circ}\text{C}$

Time: 3 sec max.

**Photocoupler  
LTV-354T series**

**8. RECOMMENDED FOOT PRINT PATTERNS (MOUNT PAD)**

Unit: mm



授权光宝代理



联系：企业QQ2881817135

电话：0755-82550289

## Photocoupler LTV-354T series

### 9. NAMING RULE

# LTV-354T-(1)-(2)-G

DEVICE PART NUMBER

(1) TAPING TYPE (TP, no suffix)

LTV-354T has tape and reel solution.

Please refer to orientation of taping on Page P3

(2) CTR RANK (A,B or none)

Please refer to Page P6

(3) Halogen free option

Example : LTV-354T-TP-A-G

# LTV 354T (1) (2)-V-G

DEVICE PART NUMBER

(1) TAPING TYPE (TP, no suffix)

LTV-354T has tape and reel solution.

Please refer to orientation of taping on Page P3

(2) CTR RANK (A,B or none)

Please refer to Page P6

(3) VDE option

(4) Halogen free option

Example : LTV354TTPA-V-G

### 10. NOTES

- LiteOn is continually improving the quality, reliability, function or design and LiteOn reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.
- When requiring a device for any "specific" application, please contact our sales in advice.
- If there are any questions about the contents of this publication, please contact us at your convenience.
- The contents described herein are subject to change without prior notice.
- Immerge unit's body in solder paste is not recommended.