


ZMY5B1...ZMY39B

Silicon Epitaxial Planar Power Zener Diodes

For use in stabilizing and clipping circuits with high power rating. Smaller voltage tolerances are upon request.

LL-41



Glass case MELF
Dimensions in mm

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Power Dissipation	P_{tot}	1 ¹⁾	W
Junction Temperature	T_j	175	°C
Storage Temperature Range	T_{stg}	- 55 to + 175	°C

¹⁾ Valid provided that electrodes are kept at ambient temperature.

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Max.	Unit
Thermal Resistance Junction to Ambient Air	R_{thA}	170 ¹⁾	K/W
Forward Voltage at $I_F = 200 \text{ mA}$	V_F	1.2	V

¹⁾ Valid provided that electrodes are kept at ambient temperature.

Characteristics at $T_a = 25^\circ\text{C}$

Type	Zener Voltage ²⁾		Dynamic Resistance		Reverse Current		Admissible Zener Current ¹⁾	
	V_Z		at I_{ZT}	Z_{ZT}	at I_{ZT}	I_R		
	Min. (V)	Max. (V)	(mA)	(Ω)	(mA)	Max. (µA)	(V)	I_{ZM} (mA)
ZMY5B1	4.99	5.2	100	5	100	10	1	150
ZMY5B6	5.49	5.71	100	2	100	0.5	2	135
ZMY6B2	6.07	6.32	100	2	100	0.5	3	128
ZMY6B8	6.66	6.94	100	2	100	0.5	4	110
ZMY7B5	7.35	7.65	100	2	100	0.5	5	100
ZMY8B2	8.04	8.36	100	2	100	0.5	6	89
ZMY9B1	8.92	9.28	50	4	50	0.5	7	82
ZMY10B	9.8	10.2	50	4	50	0.5	7.6	74
ZMY11B	10.8	11.2	50	7	50	0.5	8.4	66
ZMY12B	11.8	12.2	50	7	50	0.5	9.1	60
ZMY13B	12.7	13.3	50	9	50	0.5	9.9	55
ZMY15B	14.7	15.3	50	9	50	0.5	11.4	49
ZMY16B	15.7	16.3	25	10	25	0.5	12.2	44
ZMY18B	17.6	18.4	25	11	25	0.5	13.7	40
ZMY20B	19.6	20.4	25	12	25	0.5	15.2	36
ZMY22B	21.6	22.5	25	13	25	0.5	16.7	34
ZMY24B	23.5	24.5	25	14	25	0.5	18.2	29
ZMY27B	26.4	27.6	25	15	25	0.5	20.6	27
ZMY30B	29.4	30.6	25	20	25	0.5	22.8	25
ZMY33B	32.3	33.7	25	20	25	0.5	25.1	22
ZMY36B	35.2	36.8	10	60	10	0.5	27.4	20
ZMY39B	38.2	39.8	10	60	10	0.5	29.7	18

¹⁾ Valid provided that electrodes are kept at ambient temperature.

²⁾ Tested with pulses $t_p = 20 \text{ ms}$

