


Features

- Integrated protection ring against static discharge
- Low capacitance
- Low leakage current
- Low forward voltage drop
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

Mechanical Data

- **Case:** SOD-80 Glass case
- **Weight:** approx. 34 mg
- **Cathode Band Color:** Black
- **Packaging Codes/Options:**
GS18 / 10 k per 13" reel (8 mm tape), 10 k/box
GS08 / 2.5 k per 7" reel (8 mm tape), 12.5 k/box



SOD-80		
Dim	Min	Max
A	3.30	3.70
B	1.30	1.60
C	0.28	0.50
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics @ T_A = 25°C unless otherwise specified

Parameter	Test condition	Part	Symbol	Value	Unit		
Reverse voltage		LL103A	V_R	40	V		
		LL103B	V_R	30	V		
		LL103C	V_R	20	V		
Peak forward surge current	$t_p = 300\text{ }\mu\text{s}$, square pulse		I_{FSM}	15	A		
Power dissipation	$l = 4\text{ mm}$, $T_L = \text{constant}$		P_{tot}	400	mW		
Parameter	Test condition	Part	Symbol	Min	Typ.	Max	Unit
Reverse Breakdown Voltage	$I = 10\text{ }\mu\text{A}$	LL103A	$V_{(BR)R}$	40			V
		LL103B	$V_{(BR)R}$	30			V
		LL103C	$V_{(BR)R}$	20			V
Leakage current	$V = 30\text{ V}$	LL103A	I_R			5	μA
	$V = 20\text{ V}$	LL103B	I_R			5	μA
	$V = 10\text{ V}$	LL103C	I_R			5	μA
Forward voltage drop	$I_F = 20\text{ mA}$		V_F			370	mV
	$I_F = 200\text{ mA}$		V_F			600	mV
Diode capacitance	$V_R = 0\text{ V}$, $f = 1\text{ MHz}$		C_D		50		pF
Reverse recovery time	$I_F = I_R = 50\text{ to }200\text{ mA}$, recover to $0.1\text{ }I_R$		t_{rr}		10		ns




Figure 1. Forward Current vs. Forward Voltage




Figure 2. Forward Current vs. Forward Voltage




Figure 3. Reverse Current vs. Junction Temperature




Figure 4. Diode Capacitance vs. Reverse Voltage




Figure 5. Typ. Non Repetitive Forward Surge Current vs. Pulse width