


SPECIFICATION

Current Rating: 1.0Amp
 Insulation Resistance: 1000MΩ min
 Contact Resistance: 20MΩ max
 Withstand Voltage: 500V AC/DC
 Operating Temperature: -40° C to +105° C
 Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: PA6T+30%GF UL 94V-0

Ordering Code:


BHBS02 - X - X - X - X - X
 ① ② ③ ④ ⑤ ⑥

- ① Series No:
 ② No. of Contacts
 08 10 14 16 20 24
 26 30 34 40 50 56
 60 80 100
 ③ Contact Plating:
 G0:Gold flash S0:Selective
 G1:3U" Gold S1:Selective 3u"
 G2:5u" Gold S2:Selective 5u"
 G3:10u" Gold S3:Selective 10u"
 G4:15u" Gold S4:Selective 15u"
 G5:30u" Gold S5:Selective 30u"
 SN:Tin
 ④ Color Insulator
 B:Black
 U:Blue
 W:White
 ⑤ Insulator Material
 A:PBT
 B:PA6T
 C:LCP
 D:PA46
 E:PA9T
 ⑥ Packing
 A:Tray
 B:Bag
 T:Tube
 U:Tube+CAP
 R:Tape&Reel
 W:Tape&Reel+CAP



Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW Wu Feng Rong DATE 12/05/2020
 CHECK BobYang DATE 01/05/2016



Antenk® ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE:
 1.27*2.54mm Box Header 180° H=5.85

DRAWING NO: BHBS02-XXXXX

PRODUCT NO: BHBS02-XXXXX

REV	DESCRIPTION	DATE
1	Revise Pin No.	09/14/2023
2	Revise Dimensions	10/28/2022