



**ATTENTION**  
OBSERVE PRECAUTIONS  
FOR HANDLING  
ELECTROSTATIC  
SENSITIVE  
DEVICES



**CAUTION**

This bag contains  
MOISTURE-SENSITIVE DEVICES If blank, see adjacent  
bar code label

LEVEL  
**3**

1. Calculated shelf life in sealed bag: 12 months at  $< 40^{\circ}\text{C}$   
and  $< 90\%$  relative humidity (RH)
  2. Peak package body temperature: 260  $^{\circ}\text{C}$   
If blank, see adjacent bar code label
  3. After bag is opened, devices that will be subjected to reflow  
solder or other high temperature process must  
a) Mounted within: 168 hours of factory  
If blank, see adjacent bar code label  
conditions  $\leq 30^{\circ}\text{C}/60\%$   
b) Stored at  $< 10\%$  RH
  4. Devices require bake, before mounting, if:  
a) Humidity Indicator Card is  $> 10\%$  when read at  $23 \pm 5^{\circ}\text{C}$   
b) 3a or 3b not met
  5. If baking is required, devices may be baked for 48 hours at  $125 \pm 5^{\circ}\text{C}$   
Note: If device containers cannot be subjected to high temperature  
or shorter bake times are desired.  
reference IPC/JEDEC J-STD-033 for bake procedure
- Bag Seal Date: \_\_\_\_\_  
If blank, see adjacent bar code label
- Note: Level and body temperature defined by IPC/JEDEC J-STD-020



平芯微

Wuxi PWCHIP Semi Technology CO., LTD

Product: PW6206A33HV



Lot No: PGh23999h



D/C: 2348



Data:

2023/11/24

QTY: 3000



夸克微科技

ROHS



无锡市平芯微半导体科技有限公司  
www.pwchip.com

夸克微科技