



ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
SENSITIVE
DEVICES



CAUTION

This bag contains
MOISTURE-SENSITIVE DEVICES

LEVEL

3

If Blank, see adjacent
bar code label

1. Calculated shelf life in sealed bag: 12 months at $< 40^{\circ}\text{C}$ and $< 90\%$ relative humidity (RH)
2. Peak package body temperature: 260 $^{\circ}\text{C}$
If blank, see adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
 - a) Mounted within: 168 hours of factory
If blank, see adjacent bar code label
 - conditions $\leq 30^{\circ}\text{C}/60\%$
 - b) Stored at $< 10\%$ RH
4. Devices require bake, before mounting, if:
 - a) Humidity Indicator Card is $> 10\%$ when read at $23 \pm 5^{\circ}\text{C}$
 - b) 3a or 3b not met
5. If baking is required, devices may be baked for 48 hours at $125 \pm 5^{\circ}\text{C}$
Note: If device containers cannot be subjected to high temperature or shorter bake times are desired,
reference IPC/JEDEC J-STD-033 for bake procedure

Bag Seal Date: _____

If blank, see adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020

夸克微科技



PULAN TECHNOLOGY CO., LIMITED

Device Name : PS7516D6G



Quantity : 3000EA



Data Code : 2324



Lot No. 夸克微科技



【公司网站】

PL20230610

AMAU0FS12ZH