
Thick film rectangular

MCR10 (2012 size : 1 / 8W)

●Features

1) Power rating of 1 / 8W
2) Highly reliable chip resistor
   Ruthenium oxide dielectric offers superior resistance to the elements.
3) Electrodes not corroded by soldering
   Thick film makes the electrodes very strong.
4) Leading the world in development and mass production.
   Since start of production in 1982 (first in the wold), this component has established a solid reputation as a general–purpose chip resistor.
5) ROHM resistors have approved ISO–9001 certification.
   Design and specifications are subject to change without notice. Carefully check the specification sheet before using or ordering it.

●Ratings

Item	Conditions	Specifications
Rated power	Power must be derated according to the power derating curve in Figure 1 when ambient temperature exceeds 70°C.  Fig.1	0.125W (1 / 8W) at 70°C
Rated voltage	The voltage rating is calculated by the following equation. If the value obtained exceeds the limiting element voltage, the voltage rating is equal to the maximum operating voltage. $E=\sqrt{P\times R}$ E: Rated voltage (V) P: Rated power (W) R: Nominal resistance (Ω)	Limiting element voltage: 150V
Nominal resistance	See Table 1.	
Operating temperature		–55°C ~ + 155°C

Jumper type

Resistance	Max. 50mΩ
Rated current	2A
Operating temperature	–55°C to +155°C

Table 1


Resistance tolerance	Resistance range (Ω)	Resistance temperature coefficient (ppm/°C)
F (±1%)	0.1 ≤ R < 0.15 (E24)	400±200
	0.15 ≤ R < 10 (E24)	±250
	10 ≤ R ≤ 2.2M (E24,96)	±100
J (±5%)	0.1 ≤ R < 0.15 (E24)	400±200
	0.15 ≤ R < 1 (E24)	±250
	1.0 ≤ R < 2.2 (E24)	500±350
	2.2 ≤ R < 10 (E24)	±500
	10 ≤ R ≤ 10M (E24)	±200

●Before using components in circuits where they will be exposed to transients such as pulse loads (short–duration, high– level loads), be certain to evaluate the component in the mounted state. In addition, the reliability and performance of this component cannot be guaranteed if it is used with a steady state voltage that is greater than its rated voltage.

●Characteristics

Item	Guaranteed value		Test conditions (JIS C 5201-1)
	Resistor type	Jumper type	
Resistance	J : ±5% F : ±1%	Max. 50mΩ	JIS C 5201-1 4.5
Variation of resistance with temperature	See Table.1		JIS C 5201-1 4.8 Measurement : –55 / +25 / +125°C
Overload	± (2.0%+0.1Ω)	Max. 50mΩ	JIS C 5201-1 4.13 Rated voltage (current) ×2.5, 2s. Maximum overload voltage : 200V
Solderability	A new uniform coating of minimum of 95% of the surface being immersed and no soldering damage.		JIS C 5201-1 4.17 Rosin·Ethanol (25%WT) Soldering condition : 235±5°C Duration of immersion : 2.0±0.5s.
Resistance to soldering heat	± (1.0%+0.05Ω)	Max. 50mΩ No remarkable abnormality on the appearance.	JIS C 5201-1 4.18 Soldering condition : 260±5°C Duration of immersion : 10±1s.
Rapid change of temperature	± (1.0%+0.05Ω)	Max. 50mΩ	JIS C 5201-1 4.19 Test temp. : –55°C~+125°C 5cyc
Damp heat, steady state	± (3.0%+0.1Ω)	Max. 100mΩ	JIS C 5201-1 4.24 40°C, 93%RH Test time : 1,000h~1,048h
Endurance at 70°C	± (3.0%+0.1Ω)	Max. 100mΩ	JIS C 5201-1 4.25.1 Rated voltage (current), 70°C 1.5h : ON – 0.5h : OFF Test time : 1,000h~1,048h
Endurance	± (3.0%+0.1Ω)	Max. 100mΩ	JIS C 5201-1 4.25.3 155°C Test time : 1,000h~1,048h
Resistance to solvent	± (1.0%+0.05Ω)	Max. 50mΩ	JIS C 5201-1 4.29 23±5°C, Immersion cleaning, 5±0.5min. Solvent : 2-propanol
Bend strength of the end face plating	± (1.0%+0.05Ω)	Max. 50mΩ Without mechanical damage such as breaks.	JIS C 5201-1 4.33


●External dimensions (Units : mm)



No.	Material
①	Resistive element (Oxide metal thick film)
②	Silver palladium thick film electrode
③	Nickel electrode
④	Sn/Pb or Sn electrode
⑤	Alumina substrate
⑥	Overcoating (glass)

●Packaging

Reel




EIAJ ET-7200A compliant

(Units: mm)

A	B	C	D
$\phi 180^{\ 0}_{-3}$	$\phi 60^{\ +1}_{\ 0}$	$9^{\ +1.0}_{\ 0}$	$\phi 13 \pm 0.2$


Taping



(Units: mm)

W	F	E	A0	B0
8.0±0.3	3.5±0.05	1.75±0.1	$1.65^{+0.2}_{-0.1}$	$2.4^{+0.2}_{-0.1}$
D0	P0	P1	P2	T2
$\phi 1.5^{+0.1}_{0}$	4.0±0.1	4.0±0.1	2.0±0.05	Max. 1.1


Bulk case



EIAJ ET-7201A compliant

(Units: mm)

●Part designation



Part No.	Code	Packaging	Standard ordering Unit(pcs)
MCR10	EZH	Paper tape	5,000
	PZHI	Bulk case	10,000

F	±1%	J	±5%
Specify "J" for jumper also.			

Blank	10Ω or more (F class) 1Ω or more (J class)
L	Up to10Ω (F class) Up to1Ω (J class)

●Dimensions




Fig.2 Dimensions (length)




Fig.3 Dimensions (width)




Fig.4 Dimensions (thickness)

●Electrical characteristics




Fig.5 Resistance




Fig.6 Variation resistance with temperature




Fig.7 Overload




Fig.8 Resistance to soldering heat




Fig.9 Rapid change of temperature




Fig.10 Damp heat, steady state




Fig.11 Endurance at 70°C




Fig.12 Endurance




Fig.13 Resistance to solvents




Fig.14 Bend strength of the end face plating

电子工程世界
eeworld.com.cn
创新电子设计之源

This datasheet has been downloaded from:

datasheet.eeworld.com.cn

Free Download

Daily Updated Database

100% Free Datasheet Search Site

100% Free IC Replacement Search Site

Convenient Electronic Dictionary

Fast Search System

www.EEworld.com.cn

All Datasheets Cannot Be Modified Without Permission

Copyright © Each Manufacturing Company