

SMD Type Crystal Resonators

DSX151G SERIES



The DSX151G is a compact, highly reliable product with excellent environmental resistance and stability, consisting of a crystal resonator-mounted ceramic base and a ceramic cap sealed by low-temperature-melt glass.

■ Features

- Miniature SMD crystal resonators.
- Reliable ceramic package provides high resistance against extreme environment.


■ Generic Specification

TYPE1	DSX151GA						
TYPE2		DSX151GL					
Frequency Range	3.5~4MHz	4~5MHz	5~12MHz	12~20MHz	20~26MHz	26~33MHz	26~55MHz
Vibration Mode	Fundamental						3rd
Load Capacitance	Series, 12pF, 16pF, 20pF, 32pF						8pF, 10pF, 12pF, 16pF
Drive Level	10μW (300μW max.)						50μW (1mW max.)
Frequency Tolerance	±50×10 ⁻⁶ , ±100×10 ⁻⁶ (at 25°C)						
Series Resistance	100Ωmax.		80Ωmax.	60Ωmax.	40Ωmax.	60Ωmax.	100Ωmax.
Frequency Characteristics over Temperature	±40×10 ⁻⁶ /-10~+60°C (Ref. to 25°C)		±30×10 ⁻⁶ /-10~+60°C (Ref. to 25°C)				
	±60×10 ⁻⁶ /-20~+70°C (Ref. to 25°C)		±50×10 ⁻⁶ /-20~+70°C (Ref. to 25°C)				
	±100×10 ⁻⁶ /-30~+80°C (Ref. to 25°C)		±100×10 ⁻⁶ /-30~+80°C (Ref. to 25°C)				
Storage Temperature Range	-40~+85°C						


Packing Unit : 1000pcs./reel

Consult our sales representative for other specifications or special specifications.
Refer to page 36 for standard specification.


■ Dimensions[mm]



■ Internal Connections



■ Recommended Land Pattern [mm]



※ The DSX151G Crystal Resonator can be used for video applications.
Specifications shown above are part of the standard specifications.
For more details, please contact our sales representative.