

保电通（东莞）电子科技有限公司

PROTECTOM (DONGGUAN) ELECTORM TECHNOLOGY CO., LTD



E Series SMD0603

E Series 0603 Surface Mount PTC Devices

--3RD FLOOR, BUILDING A11, HUAZHI BRANCH, DAOJIAO TOWN,
DONGGUAN CITY--

TEL : 0769 - 88329950 88329951 88329952 FAX : 0769-
88329953

WEB SITE : WWW.BDT-E.COM E-MAIL: PROTECTOM@126.COM

2021年修订

Performance Specification

Model	Marking	Maximum							Resistance		认证
		V _{max}	I _{max}	I _{hold}	I _{trip}	P _d	Time To Trip		R _{i min}	R _{1max}	
		@25°C	@25°C	@25°C	@25°C	Typ.	Current	Time	(Ω)	(Ω)	
		(V dc)	(A)	(A)	(A)	(W)	(A)	(Sec)			UL
SMD0603E001SF60V	X	60	20	0.01	0.03	0.5	0.2	1.00	15.000	100.000	
SMD0603E002SF60V	Y	60	20	0.02	0.06	0.5	0.2	1.00	12.000	70.000	
SMD0603E002SF9V	Y	9	20	0.02	0.06	0.5	0.2	1.00	12.000	70.000	
SMD0603E002SF30V	Y	30	20	0.02	0.06	0.5	0.2	1.00	12.000	70.000	
SMD0603E003SF30V	Z	30	20	0.03	0.09	0.5	0.2	1.00	6.000	50.000	
SMD0603E003SF9V	Z	9	20	0.03	0.09	0.5	0.2	1.00	6.000	50.000	
SMD0603E004SF24V	-	24.0	20	0.04	0.12	0.5	0.20	1.00	4.000	40.000	
SMD0603E004SF30V	-	30.0	20	0.04	0.12	0.5	0.20	1.00	4.000	40.000	
SMD0603E005SF15V	1	15.0	20	0.05	0.15	0.5	0.25	1.00	3.800	30.000	
SMD0603E005SF9V	1	9.0	20	0.05	0.15	0.5	0.25	1.00	3.800	30.000	
SMD0603E005SF24V	1	24.0	20	0.05	0.15	0.5	0.25	1.00	3.800	30.000	
SMD0603E005SF33V	-	33.0	20	0.05	0.15	0.5	0.25	1.00	3.800	30.000	
SMD0603E010SF15V	1	15.0	35	0.10	0.30	0.5	0.5	1.00	0.900	6.000	
SMD0603E010SF9V	1	9.0	35	0.10	0.30	0.5	0.5	1.00	0.900	6.000	
SMD0603E010SF24V	1	24.0	35	0.10	0.30	0.5	0.5	1.00	0.900	6.000	
SMD0603E020SF9V	2	9.0	35	0.20	0.50	0.5	1.0	0.60	0.550	3.500	
SMD0603E020SF16V	2	16.0	35	0.20	0.50	0.5	1.0	0.60	0.550	3.500	
SMD0603E025SF9V	2	9.0	35	0.25	0.55	0.5	8.0	0.08	0.500	3.000	
SMD0603E025SF16V	2	16.0	35	0.25	0.55	0.5	8.0	0.08	0.500	3.000	
SMD0603E030SF6V	3	6.0	35	0.3	0.7	0.5	8.0	0.1	0.3	2.000	
SMD0603E035SF6V	3	6.0	35	0.35	0.75	0.5	8.0	0.10	0.200	1.000	
SMD0603E035SF12V	3	12.0	35	0.35	0.75	0.5	8.0	0.10	0.200	1.000	
SMD0603E040SF6V	5	6.0	35	0.40	0.80	0.5	8.0	0.10	0.150	0.900	
SMD0603E050SF6V	5	6.0	35	0.50	1.00	0.5	8.0	0.10	0.100	0.800	
SMD0603E050SF12V	5	12.0	35	0.50	1.00	0.5	8.0	0.10	0.100	0.800	
SMD0603E060SF6V	7	6.0	35	0.60	1.20	0.5	8.0	0.10	0.080	0.600	
SMD0603E065SF6V	7	6.0	35	0.65	1.30	0.5	8.0	0.10	0.070	0.550	
SMD0603E075SF6V	7	6.0	35	0.75	1.40	0.5	8.0	0.10	0.060	0.450	
SMD0603E075SF12V	7	12.0	35	0.75	1.40	0.5	8.0	0.10	0.060	0.450	
SMD0603E100SF6V	0	6.0	35	1.00	2.00	0.5	8.0	0.10	0.050	0.300	

V_{max} = Maximum operating voltage device can withstand without damage at rated current (I_{max}).

I_{max} = Maximum fault current device can withstand without damage at rated voltage (V_{max}).

I_{hold} = Hold Current. Maximum current device will not trip in 25°C still air.

I_{trip} = Trip Current. Minimum current at which the device will always trip in 25°C still air.

P_d = Power dissipation when device is in the tripped state in 25°C still air environment at rated voltage.

R_{i min/max} = Minimum/Maximum device resistance prior to tripping at 25°C.

R_{1max} = Maximum device resistance is measured one hour post reflow.

CAUTION : Operation beyond the specified ratings may result in damage and possible arcing and flame.

PPTC 使用注意事项:

- PPTC 为热敏元件, 对环境温度比较敏感, 建议在 PPTC 周围不要设计热源元件, 尽量减少外部热源的影响。
 - 请在规格书规定的参数下使用, 超出电压电流规格值, 会导致 PPTC 出现电弧, 阻值升高, 甚至烧片。
 - 规格书的电气特性, 均是基于在保电通指定测试板经过一次回流焊之后的测试; 如果客户有二次回流焊或者注塑点胶等其他热工序, 会对上述参数有一定程度的衰减, 需要验证其适用性。
 - PPTC 贴片产品是为 SMT 工艺设计的封装形式, 焊接工艺为回流焊; 要求客户遵守我们推荐的焊盘布局和回流焊配置文件。不正确的电路板布局或回流配置可能会对 PPTC 的可焊性性能产生负面影响。焊接工艺可参考保电通推荐的回流焊曲线。如果回流焊温度超过推荐的值, PPTC 将有可能受到损伤。使用手工焊及波峰焊接 PPTC 可能会导致产品焊后电阻超出规格。
 - 某些注塑料、单组份、双组份固化胶粘剂、硅胶、侵蚀性溶剂污染 PPTC 材料破坏芯片, 需要对注塑料胶料等材料牌号以及应用参数(如温度、时间等)进行验证, 以确保产品及工艺的匹配性, 确认不会影响 PPTC 性能之后方可使用。
- PPTC 在充电线端应用中, 建议使用 PP 类材料做内膜, 禁止使用 TPE 类与 PVC 类等材料做内膜。
- PPTC 贴装或使用过程中, 不建议使用洗板水或其他清洗剂进行清洗。如必须使用, 需要验证各类清洗剂、洗板水以及溶剂的适用性, 确认不会影响 PPTC 性能之后方可使用。已知对 PPTC 有影响的化学药品包括但不限于醚类、苯类、酮类以及脂类等较强溶解性、破坏性的有机化合物, 清洗后将产品放置于敞开的环境中至少 24 小时, 将残留的溶剂进行充分的挥发。
 - 装配过程中, 避免用暴力砸、挤、压、拉、扭、刺等方式作用 PPTC 本体, 以免引起 PPTC 性能衰减。
 - PPTC 元件是为电路中偶尔出现的过流而设计的, 不建议用在连续且持续过流的电路中。
 - 保电通 SMD PPTC 湿敏等级为 2 级, 为密封包装。客户如在库存中发现有包装破损的, 立即将产品隔离处理; 使用时如有余料, 需恢复之前包装状态, 做密封保存, 否则会影响产品性能导致焊后电阻越规格。
 - 产品废弃时, 可按照一般电子废弃物处理, 具体材料组成可参见 MSDS

Environmental Specifications

Test	Conditions	Resistance change
Passive aging	+85°C, 1000 hrs.	±5% typical
Humidity aging	+85°C, 85% R.H. , 168 hours	±5% typical
Thermal shock	+85°C to -40°C, 20 times	±33% typical
Resistance to solvent	MIL-STD-202,Method 215	No change
Vibration	MIL-STD-202,Method 201	No change
Ambient operating conditions : - 40 °C to +85 °C		

Maximum surface temperature of the device in the tripped state is 125 °C

Agency Approval and Environmental Compliance


Agency	File Number	Regulation	Standard
UL	pending		LCS210427075AR
TUV	pending		pending

Thermal Derating Chart


Recommended Hold Current(A) at Ambient Temperature(°C)

Model	Ambient Operation Temperature								
	-40°C	-20°C	0°C	25°C	40°C	50°C	60°C	70°C	85°C
SMD0603E001SF	0.016	0.014	0.012	0.010	0.008	0.007	0.006	0.005	0.0035
SMD0603E002SF	0.031	0.027	0.024	0.020	0.016	0.014	0.012	0.011	0.007
SMD0603E003SF	0.047	0.041	0.036	0.030	0.024	0.021	0.018	0.016	0.0108
SMD0603E004SF	0.052	0.048	0.044	0.040	0.032	0.028	0.024	0.020	0.012
SMD0603E005SF	0.065	0.060	0.055	0.050	0.040	0.035	0.031	0.025	0.015
SMD0603E010SF	0.13	0.12	0.11	0.10	0.08	0.07	0.06	0.05	0.03
SMD0603E020SF	0.27	0.25	0.23	0.20	0.17	0.14	0.12	0.10	0.07
SMD0603E025SF	0.32	0.29	0.27	0.25	0.21	0.18	0.16	0.14	0.10
SMD0603E035SF	0.47	0.41	0.38	0.35	0.29	0.26	0.24	0.20	0.14
SMD0603E040SF	0.54	0.47	0.43	0.40	0.33	0.29	0.27	0.22	0.16
SMD0603E050SF	0.67	0.59	0.54	0.50	0.41	0.37	0.34	0.29	0.20
SMD0603E060SF	0.81	0.70	0.651	0.60	0.49	0.44	0.41	0.34	0.24
SMD0603E065SF	0.87	0.76	0.71	0.65	0.54	0.48	0.44	0.37	0.26
SMD0603E075SF	0.98	0.85	0.81	0.75	0.60	0.54	0.44	0.40	0.31
SMD0603E100SF	1.19	1.13	1.08	1.00	0.80	0.72	0.59	0.54	0.43


Thermal Derating Curve



Average Time-Current Curve



Soldering Parameters



Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate(Ts max to T p)	3°C/second max.
Preheat	
-Temperature Min(Ts min)	150°C
-Temperature Max(Ts max)	200°C
-Time(Ts min to Ts max)	60~180 seconds
Time maintained above:	
-Temperature(TL)	217°C
-Time(tL)	60~150 seconds
Peak Temperature(Tp)	260°C
Ramp-Down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max
Storage Condition	0°C~30°C,30%-60%RH

Recommended reflow methods: IR, vapor phase oven, hot air oven, N2 environment for lead-free



Recommended maximum paste thickness is 0.25mm

Devices can be cleaned using standard industry methods and solvents.

Note 1: All temperature refer to topside of the package, measured on the package body surface.

Note 2: If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements

Physical Dimensions(mm.)




型號	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SMD0603E001SF60V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E002SF60V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E002SF9V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E002SF30V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E003SF30V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E003SF9V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E004SF24V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E004SF30V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E005SF15V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E005SF9V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E005SF24V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E005SF33V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E010SF15V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E010SF9V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E010SF24V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E020SF9V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E020SF16V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E025SF9V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E025SF16V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10
SMD0603E030SF6V	1.45	1.85	0.65	1.05	0.35	0.90	0.15	0.10
SMD0603E035SF6V	1.45	1.85	0.65	1.05	0.35	0.90	0.15	0.10
SMD0603E035SF12V	1.45	1.85	0.65	1.05	0.40	0.90	0.15	0.10
SMD0603E040SF6V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10
SMD0603E050SF6V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10
SMD0603E050SF12V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10
SMD0603E060SF6V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10
SMD0603E065SF6V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10
SMD0603E075SF6V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10
SMD0603E075SF12V	1.45	1.85	0.65	1.05	0.55	1.15	0.15	0.10

Termination Pad Characteristics

Terminal pad materials: Tin-plated Nickel-Copper

Terminal pad solder ability: Meets EIA specification RS186-9E and ANSI/J-STD-002 Category 3.

Recommended Pad Layout (mm.)



Packaging Quantity


Part Number	Quantity
SMD0603 E Series	4,000 or 5,000 pcs/reel

Tape & reel packaging per EIA481

Tape And Reel Specifications (mm)

Governing Specifications	EIA 481-1
W	8.0 ± 0.2
P ₀	4.0 ± 0.10
P ₁	4.0 ± 0.10
P ₂	2.0 ± 0.05
A ₀	1.05 ± 0.10
B ₀	1.85 ± 0.10
D ₀	1.55 ± 0.05
F	3.5 ± 0.05
E ₁	1.75 ± 0.10
E ₂ min.	6.25
T	0.20
T ₁ max.	0.1
K ₀	0.75/0.95 ± 0.1
Leader min.	390
Trailer min.	160
卷軸規格	
A max.	178
N min.	60
W ₁	9.0 ± 0.5
W ₂	12.0 ± 0.05
W	8.0 ± 0.2

EIA Tape Component Dimensions



Part Number System

SMD 0603 E □□□ S F □□ V

special voltage Rating(Optional)

Lead-Free

Tin-plated Nickel-Copper

Holding Current Rating

PROTECTOM

Device Dimensions: Length/width(Unit: 1/100 inch) Size1608mm / 0603 inch

Surface Mount Device

