Features


- High Speed Switching with Low Capacitances
- High Blocking Voltage with Low $R_{DS(on)}$
- Easy to parallel
- Simple to drive
- RoHS Compliant


Part NO.		HX2M300090E
V_{DS}	=	900 V
$I_D(T_c=25℃)$	=	13 A
$R_{DS(on)}$	=	270 mΩ

Benefits

- Increased Power Density
- Faster Operating Freequency
- Reduction of Heat Sink Requirements
- Higher Efficiency
- Reduced EMI

TO-252-2L





Applications

- Power Factor Correction Modules
- Switch Mode Power Supplies
- DC-AC Inverters
- High Voltage DC/DC Converters

Halogen

RoHS

Maximum ratings (T_j=25℃ unless otherwise specified)

Symbol	Parameter	Test conditions	Value	Unit
V_{DS}	Drain-Source Voltage		900	V
I_D	Continuous Drain Current	T_c=25°C T_c=100°C	13 9.2	A
I_{DM}	Peak Drain Current	Pulse width t_p limited by T_{jmax}	24	A
V_{GSmax}	Gate-Source Voltage		-8/+22	V
V_{GSop}	Recommend Gate-Source Voltage		-4/+18	V
P_{tot}	Power Dissipation	T_c=25°C T_c=100°C	57 28.5	W
T_j	Operating Junction Temperature		-40~175	°C
T_{stg}	Storage Temperature		-40~175	°C

Electrical Characteristics

Static Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	I_D=100μA, V_{GS}=0V	900			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=900V, V_{GS}=0V		1		μA
I_{GSS}	Gate-Source Leakage Current	V_{DS}=0V, V_{GS}=18V			250	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=1.33mA T_j=25°C T_j=175℃	2	3.1 2.2	4	V
$R_{DS(on)}$	Drain-Source On-State Resistance	V_{GS}=15V, I_D=4.5A T_j=25°C T_j=175℃		370 340	500	mΩ
		V_{GS}=18V, I_D=4.5A T_j=25°C T=175℃		270 298	357	

Thermal Characteristics

Symbol	Parameter	Value			Unit
		Min.	Typ.	Max.	
$R_{th(j-c)}$	Thermal Resistance from Junction to Case		2.63		°C/W

Dynamic Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
C_{iss}	Input Capacitance	V_{DS}=600V, f=1MHz, V_{GS}=0V		203		pF
C_{oss}	Output Capacitance			26		pF
C_{rss}	Reverse Transfer Capacitance			3.5		pF
$R_{G(int)}$	Internal Gate Resistance	f=1MHz		3.6		Ω
Q_g	Total Gate Charge	V_{DS}=400V, I_D=4.5A, V_{GS}=-4/18V		11.2		nC
Q_{gs}	Gate to Source Charge			2		nC
Q_{gd}	Gate to Drain Charge			5.2		nC

Switching Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
$t_{d(on)}$	Turn-On Delay Time	V_{DD}=400V, I_D=4.5A, V_{GS}=-4V/18V, R_G=2.5Ω, L=200μH		3		ns
t_r	Rise Time			8		ns
$t_{d(off)}$	Turn-Off Delay Time			6		ns
t_f	Fall Time			11		ns
E_{on}	Turn-On Energy			21		μJ
E_{off}	Turn-Off Energy			5		μJ

Reverse Diode Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
V_{SD}	Diode Forward Voltage	V_{GS}=-4V, I_{SD}=2.5A T_j=25°C T_j=175℃ V_{GS}=-4V, I_{SD}=4.5A T_j=25°C T_j=175℃		 4.0 3.6 4.5 4.0		V
I_S	Continuous Diode Forward Current	V_{GS}=-4V T_c=25°C T_c=100℃		 13 6.5		A
t_{rr}	Reverse Recovery Time	V_{GS}=-4V, I_{SD}=4.5A, V_R=400V, di/dt=1000A/μs		10		ns
Q_{rr}	Reverse Recovery Charge			56		nC
I_{rrm}	Peak Reverse Recovery Current			4		A

Typical Performance




Figure 1. **Output Characteristics T_j=-40°C**




Figure 2 **Output Characteristics**




Figure 3. **Output Characteristics T_j=175°C**




Figure 4. **Normalized On-Resistance vs. Temperature**

Typical Performance




Figure 5. **On-Resistance vs. Drain Current For Various Temperatures**




Figure 6. **On-Resistance vs. Temperature For Various Gate Voltage**




Figure 7. **Transfer Characteristic for Various Junction Temperatures**




Figure 8. **Body Diode Characteristic T_j=-40°C**

Typical Performance




Figure 9. **Body Diode Characteristic T_j=25°C**




Figure 10. **Body Diode Characteristic T_j=175°C**




Figure 11. **Threshold Voltage vs. Temperature**




Figure 12. **Gate Charge Characteristics**

Typical Performance




Figure 13. **3rd Quadrant Characteristic T_j=-40°C**




Figure 14. **3rd Quadrant Characteristic T_j=25°C**




Figure 15. **3rd Quadrant Characteristic T_j=175°C**




Figure 16. **Output Capacitor Stored Energy**

Typical Performance




Figure 17. **Capacitances vs. Drain-Source**




Figure 18. **Continuous Drain Current Derating vs. Case Temperature**




Figure 19. **Maximum Power Dissipation Derating vs. Case Temperature**




Figure 20. **Transient Thermal Impedance**

Typical Performance




Figure 21. **Clamped Inductive Switching Energy vs. Drain Current**




Figure 22. **Clamped Inductive Switching Energy vs. R_G**




Figure 23. **Switching Times vs. R_G**





Figure 24. **Safe Operating Area**

Package Outlines



SYMBOL	Unit: mm		
	MIN	NOM	MAX
A	2.20	2.30	2.38
A1	0	-	0.10
A2	0.90	1.01	1.10
b	0.72	-	0.85
b1	0.71	0.76	0.81
b2	0.72	-	0.90
b3	5.13	5.33	5.46
c	0.47	-	0.60
c1	0.46	0.51	0.56
c2	0.47	-	0.60
D	6.00	6.10	6.20
D1	5.25	-	-
E	6.50	6.60	6.70
E1	4.70	-	-
e	2.186	2.286	2.386
H	9.80	10.10	10.40
L	1.40	1.50	1.70
L1	2.90 REF		
L2	0.508 BSC		
L3	0.90	-	1.25
L4	0.60	0.80	1.00
L5	0.15	-	0.75
L6	1.80 REF		
θ	0°	-	8°
θ1	5°	7°	9°
θ2	5°	7°	9°

Revision History

Document Version	Date of Release	Description of Changes
Preliminary	2025-05-19	Release of the datasheet.

MacroCore Semiconductor Ltd.
Suzhou, China
All Rights Reserved.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest MCS office.

Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device. Hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.